

Code 275Custom-316-C

Category Custom Made

Channel Material Stainless Steel

Grates longer than 1500mm supplied in sections. Tile Inserts

longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on

Grate Style CR

Steel Grade 316

dimensions

Range Custom Fabrication



275Custom-316-C

Linear Drain



Available with a 5mm wire x 5mm gap and 5mm wire x 5mm gap Grate Grip slip resistant dimple finish

Suits Load Class C.

For site specific needs or unusual situations, choose from our Custom Fabrication range.

Stormtech can customise any drainage requirements to achieve maximum efficiency



Channel Width 285mm **Channel Depth** 60mm - 285mm As Required

DN40, DN50, DN65, DN80, DN100



Length(s)

Outlet Size

STORMTECH COLOUR FINISHES





Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

PRODUCT APPLICATIONS

Bathroom Drainage Aged / Health Care Drainage **Balcony Drainage** Commercial Drainage Courtyard / Patio Drainage Driveway Drainage

Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 13/07/2025 (please check for updates)





